

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 February 2005 (17.02.2005)

PCT

(10) International Publication Number
WO 2005/015543 A1

(51) International Patent Classification⁷: **G10L 11/00**,
15/02

(21) International Application Number:
PCT/DK2004/000526

(22) International Filing Date: 6 August 2004 (06.08.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PA 2003 01136 6 August 2003 (06.08.2003) DK

(71) Applicant and

(72) Inventor: **LEONHARD, Frank, Uldall** [DK/DK]; Louis-
sevej 13, DK-2800 Lyngby (DK).

(74) Agent: **ZACCO DENMARK A/S**; Hans Bekkevolds Allé
7, DK-2900 Hellerup (DK).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, GR, GU, HK, HN, IL, IN, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MY, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: METHOD FOR ANALYSING SIGNALS CONTAINING PULSES



(57) Abstract: The invention provides a method for analysing an input signal having an input frequency bandwidth. The method comprises providing at least one frequency-bandwidth limited portion of the input signal. For each frequency-bandwidth limited portion of the input signal the durations of half-periods and signal excursions during respective half-periods are determined. Based on the signal excursions and corresponding half-periods a quality of the input signal is determined. The determined signal quality can be a vowel in a 10 speech signal or a quality related to a condition of an industrial product. The method provides speaker independent vowel recognition, and even whistled vowels can be recognised.

WO 2005/015543 A1